

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128 (Std) UMW508 (+2mm High Mount)

Steering plate: Std. UMW701

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: _____ mm

4.8mm Ball Stud Spacer: _____ mm

Axle Spacer: Out _____ mm In _____ mm

Wheel Hub: _____ mm

Steering Knuckle: Std. UMW702

Bump Steer Spacer: _____ mm

Toe: In Out _____ °

Tie Rod: _____

Front Bulkhead Weight Placement: None Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block position: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: _____ mm _____ mm

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Sway Bar: None _____ mm

Upper Spacer: _____ mm

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 Wide RF2 UMW514+UMW515

Universal Swing Shaft: _____

Camber: _____ °

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Rear Hub: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Axle Spacer: Out _____ mm In _____ mm

RR: _____

Mid: _____

Comments: _____

Motor Position

- Rear Motor Midship Motor

Diff.

- Gear Diff. # _____ Ball Diff.

Shock

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	_____	_____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ mm	out _____ mm	in _____ mm	out _____ mm
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Length(B):	_____ mm	_____ mm	_____ mm	_____ mm
O-ring:	_____	_____	_____	_____
Ball End type: Front:	S <input type="checkbox"/> M <input type="checkbox"/> L <input type="checkbox"/>			
Rear:	S <input type="checkbox"/> M <input type="checkbox"/> L <input type="checkbox"/>			

Battery Placement:

- None Screw
- Front Rear
- Foam: Front Rear None

Battery Type

- Straight Separate Short
- Type: _____

Chassis

F _____ mm Ride Height: R _____ mm

Other

Motor: _____

ESC: _____

Pinion/Spur: _____

Truck Condition

- Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groore Higt Truction Clay Wet Dusty Dry Other

Wing

- Blast-S Wing Mount : Blast-L Narrow Step-S Wide Step-M Wing Angle : Step-L 4° Step 2.0 7° 10°
- Lip : _____

Tire

Tire: _____ Front _____ Rear _____

Inserts: _____ Traction Compound or comment: _____

Wheel: _____

Comment
