

Name of Driver		Date	Track		Engine	Plug		Muffler	
YUTA HISAMOTO		2022.11.27	RC Land TAKI		O.S B2104	O.S P3		O.S T-2100	
			Condition: _____	Temperature: _____					
Spur Gear	Clutch Bell	Clutch Spring		Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
46 T	☐ Std. ☒ LW	☐ 0.90 ☒ 1.00	Carbon <u> x 1 </u>	Tire : <u> JETKO </u>	JETKO	JETKO	TKI2	KLOTZ	
	13 T	☐ 0.95 ☐ 1.10	Aluminum <u> x 2 </u>	Compounds: <u> US </u>					

● Diff. Gear Set-Up

	Front		Center		Rear	
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD		☒ 10/20 ☐ 12/18 ☐ LSD		☒ 10/20 ☐ 12/18 ☐ LSD	
	Ring Gear ☐ 43/13 ☐ 42/12	# 7000	Diff. Size ☐ Small ☒ Large	# 6000	Ring Gear ☐ 43/13 ☒ 42/12	# 4000

● Shock Set-Up

		Front		Rear	
Shock Type	P : w/Diaphragm A : Aeration	Size 47	type - P	Size 55	type - P
Shock Piston	B : Black W : White T : Taper	B φ 1.2 x 6		W φ 1.3 x 6	
Shock Oil		#	500	#	550
Shock Spring		IFS005-8516		IFS006-10516	

- Ride Height

Front	Rear
24 mm	26 mm

- Rebound

Front	Rear
103 mm	118 mm

- Camber Angle

Front	Rear
+	+
-	-

● Toe Angle

Front	Rear
+ ° - °	 2.5° ☐ 3° ☐ 3.5°

- Wheelbase

Collar of Rear Hub	Front Side <u>5</u> mm
	Rear Side <u>0</u> mm

● Shock Mount Position

<Front> **<Rear>**

Sus. Arm

Front	☐ In	☒ Out
Rear	☒ In	☐ Out

- Rear Upper Arm Position

● Rear Wheel Hub

☒ Narrow
 ☐ Std.
 ☐ Wide

- Front Sus. Arm

☐ SS ☒ Soft (Std.) ☐ Hard

- Front Sus. Bush

Rear Side	 	 
-----------	---	--

● Front Upper Arm Position

● Front Wheel Hub

☒ Narrow ☐ Std. ☐ Wide

- Rear Sus. Bush

Front Side	    
Rear Side	             

- Rear Sus. Arm

☒ Soft (Std.)	☐ Hard
Rear Sus. Bush	
☐ Short	
☐ Medium	
☒ Long	

- Steering Plate

A schematic diagram of a double-headed spine model. It consists of two identical segments connected by a central joint. Each segment has a circular vertebra in the middle and a series of four rectangular blocks at each end. The leftmost block is highlighted in red. An arrow labeled 'Front' points upwards from the center joint, indicating the anterior direction.

● Weight

Front	Rear
☐ None	☐ None
☐ IFW604-10	☐ IFW605-10
☒ IFW604-20	☒ IFW605-20
☐ other	☐ other

- Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☐ 16° ☒ 17.5° ☐ 19° ☐ 22°

A line drawing of a right hand, palm facing up. Six numbered callouts point to specific features: 1 points to the thumb, 2 points to the index finger, 3 points to the middle finger, 4 points to the ring finger, 5 points to the pinky finger, and 6 points to the wrist area.

● Servo Horn

Steering	Throttle
☐ Plastic	☐ Plastic
☐ AL. Long	☒ AL.
☒ AL. Short	

- Sway Bar

Front	Rear
$\varnothing$ 2.4	$\varnothing$ 2.6
0 mm	1 mm

- Wing

■ IF491(TKI4) Flap ■ None
 5mm
 8mm
○ Holes

memo: