

ULTIMA RB5 SP SET UP SHEET



Name Kohta Akimoto Date 20/AUG/2010 Truck / City YATABE ARENA Event _____

Front Suspension

Upper Spacer 2.0 mm
 4.8mm Ball Stud
 Standard(UM128)
 High Mount (+2mm:UMW508)

Shock Stay
 Std(UM511)
 C-Comp(UMW500)

Toe In Out 0 °

Front Bulkhead Weight Placement
 None
 Bulkhead Inside _____ oz 10 g * 1oz=28g
 On the skid plate _____ oz 5 g

Camber + - 1 °

Ackerman Steer Spacer 0 mm
 Bump Steer Spacer 0 mm

Axle Type
 Standard(Steel:UM506)
 Option(Aluminum:UMW507)

Axle Spacer
 Out(Standard) _____ mm
 In 1 mm

Axle Height Spacer
 Up _____ mm
 Down _____ mm

Caster Spacer
 25 ° 0.5
 30 ° 1.0
 None

Comments: _____

Rear Suspension

Lower Sus Holder
 Normal RF:RB5 Aluminum(Opt) UMW511+UMW512
 Wide RF2:RB5SP UMW514+UMW515

Upper Spacer 3.0 mm

Wing Height
 1
 2
 3

Sus Holder Spacer
 F 0.5 1.0
 R 0.5 1.0
 None None

Anti-Squat _____ °

Swing Shaft
 62.5mm:RB5(UM510,UM510-01)
 65.5mm:RB5SP(UM522,LA232-01)

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0 ° (Standard)
 0.5 ° (LA244-05)

Sway Bar None _____ mm

Shock Stay
 Std:RB5(UM512)
 Std C-Comp:RB5-opt(UMW501)
 Short:RB5SP(UM520)

Upper Spacer 2 mm

Lower Arm
 Short:RB5(UM503)
 Middle:RB5SP(UM521)

Axle Spacer
 Out _____ mm
 In 0.3 mm

Wheel Shaft Type
 RB5SP(UM522-02)
 RB5(UM510-02)
 Type-B(UM519)
 Up(LA244-05)
 Middle
 Down
 Type-B2

Wheel Spacer _____ mm
 _____ mm for PL-Wheel (UMW502)

Comments: _____

Shock

	Front	Rear
Shock Piston	2 - B	2 - C
Shock Oil	# 50 (Xgear RED)	# 45 (Xgear RED)
Shock Spring	Pink (Xgear)	Pink (Xgear)
Limiters	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A)	_____ mm	_____ mm
Shaft Length(B)	20.0 mm	28.0 mm
Shock Top Type	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS	
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP (W5196-01V) 38mm <input type="checkbox"/> STD:RB5 (W5187-01V) 42mm	
Rear Shock Shaft	<input checked="" type="checkbox"/> STD:RB5SP (W5193-01) 50mm <input type="checkbox"/> Opt:ZX5 (W5183-02) 54mm	

Body / Wing / Chassis

Wing
 Aquarius(LA239)
 Sagittarius(LA240)
 Aries(LA241)
 Blast-L(LA251)
 Step-L(LA247)
 Step-S(LA247)
 Blast-S(LA247)
 Other: Step-M

Body
 Trident:RB5(UMB01)
 Sword:RB5SP(UMB02)
 Other: _____

Battery Placement
 Front Rear

Weight Placement * 1oz=28g

 Ride Height A B F 24 mm R 23.5 mm

Truck Condition

<input type="checkbox"/> Smooth	<input type="checkbox"/> Sandy	Kind in spring #55 Orange #60 Orange Yellow #65 Yellow #68 Blue #70 Silver #72 Cobalt blue #75 Light Green #80 Green
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt	
<input type="checkbox"/> Low Truction	<input type="checkbox"/> Grass	
<input type="checkbox"/> Med. Truction	<input type="checkbox"/> Blue Groove	
<input type="checkbox"/> Higt Truction	<input type="checkbox"/> Clay	
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty	
<input type="checkbox"/> Dry	<input type="checkbox"/> Other	

Tire	Front	Rear	Others
Tire	_____	_____	Motor <u>ORION 2009 8.5T</u>
Inserts	_____	_____	Pinion/Spur <u>22 / 78</u>
Wheel	_____	_____	Battery <u>PEAK 5400 Lipo</u>
Traction Compound	_____	_____	ESC <u>KO BMC</u>
Comment : _____			