

# ULTIMA RB5 SP SET UP SHEET



Name Shin Adachi Date 11/AUG/2010 Truck / City YATABE ARENA Event \_\_\_\_\_

## Front Suspension

Upper Spacer 0.5 mm  
 4.8mm Ball Stud  
 Standard(UM128)  
 High Mount (+2mm:UMW508)  
 Shock Stay  
 Std(UM511)  
 C-Comp(UMW500)  
 Camber  +  - 1°  
 Axle Type  
 Standard(Steel:UM506)  
 Option(Aluminum:UMW507)  
 Ackerman Steer Spacer  
 Low mount ball stud 0 mm  
 Bump Steer Spacer 0 mm  
 Axle Spacer  
 Out(Standard) \_\_\_\_\_ mm  
 In 1 mm  
 Axle Height Spacer  
 Up \_\_\_\_\_ mm  
 Down \_\_\_\_\_ mm  
 Toe  In  Out 1°  
 Front Bulkhead Weight Placement  
 None  
 Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g  
 On the skid plate 1/2 oz 14 g  
 Caster Spacer  
 25°  0.5  
 30°  1.0  
 None  
 Comments: \_\_\_\_\_

## Rear Suspension

Lower Sus Holder  
 Normal  RF:RB5  Aluminum(Opt) UMW511+UMW512  
 Wide  RF2:RB5SP  UMW514+UMW515  
 Wing Height  
 1  
 2  
 3  
 Upper Spacer 3.25 mm  
 Wheelbase  
 Long  
 Middle  
 Short  
 Rear Hub add Toe  
 0° (Standard)  
 0.5° (LA244-05)  
 Sway Bar  None  \_\_\_\_\_ mm  
 Sus Holder Spacer  
 0.5  0.5  
 F  1.0 R  1.0  
 None  None  
 Camber  +  - 1°  
 Anti-Squat \_\_\_\_\_°  
 Swing Shaft  
 62.5mm:RB5(UM510,UM510-01)  
 65.5mm:RB5SP(UM522,LA232-01)  
 Axle Spacer  
 Out \_\_\_\_\_ mm  
 In \_\_\_\_\_ mm  
 Wheel Shaft Type  
 Wheel Spacer  RB5SP(UM522-02) \_\_\_\_\_ mm  
 RB5(UM510-02) \_\_\_\_\_ mm  
 Type-B(UM519)  
 Up(LA244-05)  
 Middle  
 Down  
 Type-B2  
 Lower Arm  
 Short:RB5(UM503)  
 Middle:RB5SP(UM521)  
 Comments: \_\_\_\_\_

Comments: \_\_\_\_\_

## Shock

	Front	Rear
Shock Piston	2 - C	2 - C
Shock Oil	# 45 (Xgear RED)	# 40 (Xgear RED)
Shock Spring	Silver (Xgear)	Pink (Xgear)
Limiters	in _____ mm out 0.5 mm	in _____ mm out 0.5 mm
Shock Length(A)	_____ mm	_____ mm
Shaft Length(B)	20.0 mm	28.0 mm
Shock Top Type	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
	Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS	
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP (W5196-01V) 38mm <input type="checkbox"/> STD:RB5 (W5187-01V) 42mm	
Rear Shock Shaft	<input checked="" type="checkbox"/> STD:RB5SP (W5193-01) 50mm <input type="checkbox"/> Opt:ZX5 (W5183-02) 54mm	

## Body / Wing / Chassis

Wing  
 Aquarius(LA239)  
 Sagittarius(LA240)  
 Aries(LA241)  
 Blast-L(LA251)  
 Step-L(LA247)  
 Step-S(LA247)  
 Blast-S(LA247)  
 Other: Step-M

Body  
 Trident:RB5(UMB01)  
 Sword:RB5SP(UMB02)  
 Other: \_\_\_\_\_

Battery Placement  
 Front  Rear

Wing Angle  
 4°  7°  10°

Weight Placement \* 1oz=28g  
  
 Ride Height  A  B F 24 mm R 22 mm

## Truck Condition

- |  |                                      |
|--|--------------------------------------|
| <input type="checkbox"/> Smooth        | <input type="checkbox"/> Sandy       |
| <input type="checkbox"/> Bumpy         | <input type="checkbox"/> Soft Dirt   |
| <input type="checkbox"/> Low Truction  | <input type="checkbox"/> Grass       |
| <input type="checkbox"/> Med. Truction | <input type="checkbox"/> Blue Groore |
| <input type="checkbox"/> Higt Truction | <input type="checkbox"/> Clay        |
| <input type="checkbox"/> Wet           | <input type="checkbox"/> Dusty       |
| <input type="checkbox"/> Dry           | <input type="checkbox"/> Other       |

## Kind in spring

- |     |               |
|-----|---------------|
| #55 | Orange        |
| #60 | Orange Yellow |
| #65 | Yellow        |
| #68 | Blue          |
| #70 | Silver        |
| #72 | Cobalt blue   |
| #75 | Light Green   |
| #80 | Green         |

## Tire

	Front	Rear
Tire	_____	_____
Inserts	_____	_____
Wheel	_____	_____
Traction Compound	_____	_____

## Others

gear ratio =2.6  
 Motor ORION 2009 7.5T  
 Pinion/Spur 22 / 78  
 Battery ORION 5400 Lipo  
 ESC LRP SXX(1-1-1-4)

Comment : Shock ball end M