

Name Yusuke Sugiura Date 2013/09/01 Truck / City Yatabe Arena Event 2013JapanNat's

### Front Suspension

Upper Spacer: 1.5 mm

4.8mm Ball Stud:  UM128 (Std)  UMW508 (+2mm High Mount)

Camber: 1 °

Axle Spacer:  Out 0 mm  In \_\_\_\_\_ mm ※UMW701:アルミSTプレート

4.8mm Ball Stud Spacer: 0.5 mm

Wheel Hub: Std mm

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 1.5 mm

Toe:  In  Out 0 °

Tie Rod: \_\_\_\_\_

Front Bulkhead Weight Placement:  None  Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g  On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g

Caster:  25°  30°

Spacer:  0.5  1.0  None

Caster Block:  0°  2°  4°

Caster Block position:  IN (wide/Std)  OUT (Narrow)

Axle Height Spacer:  1.5 mm  \_\_\_\_\_ mm

Comments: \_\_\_\_\_

Wheelbase: F: 0 mm R: 1 mm

### Rear Suspension

Sus Holder Spacer: F  0.5  1.0  None R  0.5  1.0  None

Anti-Squat: \_\_\_\_\_ °

4.8mm Ball Stud:  UM129  UMW508 (+2mm High Mount)  97050M  UM128 (Std)

Sway Bar:  None  \_\_\_\_\_ mm

Universal Swing Shaft: \_\_\_\_\_

Camber: 1.5 °

Upper Spacer: 2 mm

Wheelbase: F: 1 mm R: 3 mm

RR: \_\_\_\_\_

Mid: \_\_\_\_\_

Lower Sus Holder: Normal  RF  Aluminum(Opt) UMW511+UMW512 Wide  RF2  UMW514+UMW515

Upper Spacer: 1 mm

Axle Spacer:  Out \_\_\_\_\_ mm  In 0.3 mm

Rear Hub add Toe:  0° Type-B (UM519)  0° Type-B2 (UM519-2)  0° Alu (UMW516-0)  0.5° Alu (UMW516-05)  1° Alu (UMW516-1)

Comments: UMW705(B), UMW707(OUT\_B)アルミサスホルダー

※UMW704-0 V2アルミリヤハブキャリア0°

Motor Position	Diff.
<input type="checkbox"/> Rear Motor	<input type="checkbox"/> Gear Diff. # _____
<input checked="" type="checkbox"/> Midship Motor	<input checked="" type="checkbox"/> Ball Diff.

### Shock

Front	Rear
Shock Piston: <u>2×1.6mm</u>	Shock Piston: <u>2×1.6mm</u>
Shock Oil: <u># 35 (Losi)</u>	Shock Oil: <u># 30 (Losi)</u>
Shock Spring: <u>Pink</u>	Shock Spring: <u>Red</u>
Limiters: in <u>0</u> mm out <u>0</u> mm	Limiters: in <u>0</u> mm out <u>0</u> mm
Shock Length(A): <u>20.5</u> mm	Shock Length(A): <u>28.0</u> mm
Shock Length(B): _____ mm	Shock Length(B): _____ mm
O-ring: <u>ORG03X (クリア)</u>	O-ring: <u>ORG03X (クリア)</u>
Ball End type: Front: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L <input type="checkbox"/> O	Ball End type: Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L <input type="checkbox"/> O

※W5303-08 フランクピストン使用

### Battery Placement:

None  Screw

Front Rear

Foam:  Front  Rear  None

### Battery Type

Straight  Separate  Short

Type: Muchmore 5000

### Chassis

ビスは説明書通り

F: 24 mm Ride Height: R: 23.5 mm

### Other

Motor: FLETA 7.5T

ESC: FLETA PRO

Pinion/Spur: 20/78

### Tire

Front	Rear	Traction Compound or comment:
Tire: <u>T-720C</u>	Tire: <u>T-755C</u>	
Inserts: <u>ProLine molded</u>	Inserts: <u>ProLine molded</u>	
Wheel: <u>Normal</u>	Wheel: <u>Normal</u>	

### Comment

・ホディピンはRB6ノーマル(※ベルクロ固定)

・バッテリーは一番後ろで固定

### Truck Condition

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Traction	<input type="checkbox"/> Blue Groove
<input checked="" type="checkbox"/> High Traction	<input checked="" type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Other

### Wing

Wing Mount:  Narrow  Wide

Wing Angle:  4°  7°  10°

Lip: PROTO