

ULTIMA RB5 SP SET UP SHEET



Name _____

Date _____

Truck / City _____

Event _____

Front Suspension

Upper Spacer _____ mm

4.8mm Ball Stud
 Standard (UM128)
 High Mount (+2mm: UM508)

Shock Stay
 Std (UM511)
 C-Corp (UM500)

Toe In Out _____ °

Front Bulkhead Weight Placement
 None
 Bulkhead Inside _____ oz _____ g * 1oz=28g
 On the skid plate _____ oz _____ g

Camber + - _____ °

Ackerman Steer Spacer _____ mm

Axle Type
 Standard (Steel: UM506)
 Option (Aluminum: UM507)

Bump Steer Spacer _____ mm

Axle Spacer
 Out (Standard) _____ mm
 In _____ mm

Axle Height Spacer
 Up
 Down

Caster
 25° 30°
 0.5 1.0
 None

Comments: _____

Rear Suspension

Lower Sus Holder
 Normal RF:RB5
 Wide RF2:RB5SP
 Aluminum (Opt) UM511+UM512
 UM514+UM515

Wing Height
 1
 2
 3

Sus Holder Spacer
 0.5 0.5
 1.0 1.0
 None None

Anti-Squat _____ °

Swing Shaft
 62.5mm:RB5 (UM510, UM510-01)
 65.5mm:RB5SP (UM522, LA232-01)

Upper Spacer _____ mm

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0° (Standard)
 0.5° (LA244-05)

Sway Bar None
 _____ mm

Carber + - _____ °

Wheel Shaft Type
 RB5SP (UM522-02)
 RB5 (UM510-02)
 for PL-Wheel (UM502)

Wheel Spacer _____ mm
 Type-B (UM519)
 Up (LA244-05)
 Middle
 Down

Lower Arm
 Short:RB5 (UM503)
 Middle:RB5SP (UM521)

Comments: _____

Shock

Shock	Front		Rear	
	in	mm	in	mm
Shock Piston	-	-	-	-
Shock Oil	# _____		# _____	
Shock Spring				
Limiters	in	mm	in	mm
	out	mm	out	mm
Shock Length(A)	_____ mm		_____ mm	
Shaft Length(B)	_____ mm		_____ mm	
Shock Top Type	<input type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/>	
	Std:RB5 Low:ZX5FS		Std:RB5 Low:ZX5FS	
Rear Shock Body	<input type="checkbox"/> Short:RB5SP(M5196-01V)38mm		<input type="checkbox"/> STD:RB5(M5187-01V)42mm	
Rear Shock Shaft	<input type="checkbox"/> STD:RB5SP(M5193-01)50mm		<input type="checkbox"/> Opt:ZX5(M5183-02)54mm	

Body / Wing / Chassis

Wing Angle 4° 7° 10°

Wing
 Aquarius (LA239)
 Sagittarius (LA240)
 Aries (LA241)
 Blast-L (LA251)
 Step-L (LA247)
 Step-S (LA247)
 Blast-S (LA247)
 Other: _____

Body
 Trident:RB5 (UMB01)
 Sword:RB5SP (UMB02)
 Other: _____

Battery Placement
 Front Rear

Weight Placement * 1oz=28g

Ride Height A B F _____ mm R _____ mm

Tire

Tire	Front		Rear	
	_____	_____	_____	_____
Inserts	_____	_____	_____	_____
Wheel Traction Compound	_____	_____	_____	_____

Others gear ratio =2.6
 Motor _____
 Pinion/Spur _____ / _____
 Battery _____
 ESC _____

Truck Condition

- | | |
|--|--------------------------------------|
| <input type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Traction | <input type="checkbox"/> Grass |
| <input type="checkbox"/> Med. Traction | <input type="checkbox"/> Blue Groove |
| <input type="checkbox"/> High Traction | <input type="checkbox"/> Clay |
| <input type="checkbox"/> Wet | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Dry | <input type="checkbox"/> Other |

Kind in spring

#55	Orange
#60	Orange Yellow
#65	Yellow
#68	Blue
#70	Silver
#72	Cobalt blue
#75	Light Green
#80	Green

Comment: _____