

ULTIMATE RB5 SP SET UP SHEET

KYOSHO
THE FINEST R/C CAR CONTROL MODELS

Name
Shin Adachi

Date
2009/07/1

Truck / City
YATABE

Event

Front Suspension

Upper Spacer _____ mm

Shock Stay
 Std (UM511)
 C-Comp (UMW500)

Toe In Out 0.5°

Front Bulthead Weight Placement
 None
 Bulthead Inside _____ oz _____ g * 1oz=28g

Upper Spacer
 4.8mm Ball Stud
 Standard (UM128)
 High Mount (+2mm: UMW508)

Camber + - 0.5°

Caster Spacer
 25°
 30°
 1.0
 None

Axle Type
 Standard (Steel: UM506)
 Opt: on (Alum: UMW507)

Axle Spacer
 Out (Standard) _____ mm
 In _____ mm

Ackerman Steer Spacer _____ mm

Bump Steer Spacer _____ mm

Axle Height Spacer
 Up
 Down

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0° (Standard)
 0.5° (LA244-05)

Sway Bar None _____ mm

Comments: Axle Height is Middle

Rear Suspension

Normal Narrow Wide

Lower Sus Holder
 RE: RB5
 RF2: RB5SP
 Alum: num (Opt)
 UMW511+UMW512
 UMW514+UMW515

Sus Holder Spacer
 0.5
 1.0
 None

Swing Shaft
 62.5mm: RB5 (UM510, UM510-01)
 65.5mm: RB5SP (UM522, LA232-01)

Anti-Squat 2 °

Camber + - 1.0°

Axle Spacer
 Out _____ mm
 In _____ mm

Wheelbase
 Long
 Middle
 Short

Rear Hub add Toe
 0° (Standard)
 0.5° (LA244-05)

Sway Bar None _____ mm

Upper Spacer _____ mm

Wheel Shaft Type
 RB5SP (UM522-02)
 RB5 (UM510-02)
 for PL-Wheel (UMW502)

Lower Arm
 Short: RB5 (UM503)
 Middle: RB5SP (UM521)

Wheel Spacer _____ mm

Wheel Shaft Type

Comments:

Shock

Shock Piston 2-B

Shock Oil # X-SPARK 7.5

Shock Spring in _____ mm out _____ mm

Limiters in _____ mm out _____ mm

Shock Length (A) _____ mm

Shaft Length (B) 20 mm

Shock Top Type
 Std: RB5 Low: ZX5FS
 Short: RB5SP (M5196-01V) 38mm
 STD: RB5 (M5187-01V) 42mm

Rear Shock Body
 STD: RB5SP (M5193-01) 50mm
 Opt: ZX5 (M5183-02) 54mm

Rear Shock Shaft

Body / Wing / Chassis

Wing
 Aquarius (LA239)
 Sagittarius (LA240)
 Aries (LA241)
 Blast-L (LA251)
 Step-L (LA247)
 Step-S (LA247)
 Blast-S (LA247)
 Other: _____

Body
 Trident: RB5 (UMB01)
 Sword: RB5SP (UMB02)
 Other: _____

Battery Placement
 Front Rear

Weight Placement * 1oz=28g

Wing Angle
 4° 7° 10°

Ride Height A B 24 mm 22 mm

Tire
 Front 1.8-4- Rear 1.8-4-

Inserts Std Std

Wheel Std Std

Traction Compound _____

Others gear ratio =2.6
 Motor VERTX 2008 6.5
 Pinion/Spur 21 / 78
 Battery SHO420 EU
 ESC LBP-SXX

Kind in spring

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy	#55	Orange
<input checked="" type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt	#60	Orange Yellow
<input checked="" type="checkbox"/> Low Truaction	<input type="checkbox"/> Grass	#65	Yellow
<input checked="" type="checkbox"/> Med. Truaction	<input type="checkbox"/> Blue Groore	#68	Blue
<input type="checkbox"/> Higt Truaction	<input checked="" type="checkbox"/> Clay	#70	Silver
<input checked="" type="checkbox"/> Wet	<input type="checkbox"/> Dusty	#72	Cobalt blue
<input checked="" type="checkbox"/> Dry	<input type="checkbox"/> Other	#75	Light Green
		#80	Green