

V-ONE R4EVO.2

SET UP SHEET Ver 1.00

Name	T.KAMETANI	Temp	°C	Engine	12TG.ver4	Muffler	T-1080&MT03
Date	2020/04/04	Humidity	%	Head Clearance	0.2 mm	Fuel Type	OS 25%
Track	SRT	Traction	%	Plug No.	No.4	Radio	SANWA M17

Shock Position A B C D E

Weight Position

Servo Saver (R) 0 0.5 1.0

Caster Angle (Caster Spacer) F

Wheel Base

Bump Steering

Shock Type	N(Short) W5307-06
Shock Oil	650
Shock Piston	N 3-1.1(W5307-09)
Spring	W5307-33Yellow
Ball End Type	S
Shock Position	A B C D E
Caster Angle(Spacer)	0.5 mm
Camber Angle 0G/1G	L 0 0.5 1 1.5 2 R 0 0.5 1 1.5 2
Toe Angle	-1 deg
Front Width	197 mm
Down Stop	-1.5 mm
Wheel Spacer	0 mm
Antiroll Bar	VZ084SS VZ084S VZ084
Tire	AMR-HOT RACE BI
Tire Inner	
Chassis Height	6mm/60 mm
Weight Position	mm
Front Diff. Oil	VZW447(FTT)+300000

Upper Arm Spacer (Out)

Chassis Height

Down Stop

Upper Arm Position (In)

Wheel Spacer

Upper Arm Position (In) for VZW433

Sus.Holder Spacer

Wheel Base

Weight

Shock Type	W5302-02+0.5Washer
Shock Oil	700
Shock Piston	N 3-1.1(W5307-09)
Spring	W5308-154Purple
Ball End Type	S
Shock Position	A B C D E F G H I
Wheel Spacer	
Upper Arm Position (In)	VZW433 Middle hole
Upper Arm Spacer (Out)	1.5 mm
Camber Angle 0G/1G	L 3 deg R 3 deg
Toe Angle	3 deg
Rear Width	199 mm
Down Stop	+1 mm
Antiroll Bar	N 2.1 mm
Tire	AMR-HOT RACE37
Tire Inner	
Chassis Height	7.5mm/62 mm
Lower Arm Position	⊙(ZERO) ⊙(OUT) N R0.7 mm
Weight	
Wheel Base	N 1mm long
Body	PF P47 6mm forward

Clutch Type	VZW442+VZW488	Pinion Gear	AL. STEEL 15 16 17 / 20 21 22 23
Clutch Shoe	VZW442-04TG	Spur Gear	59 60 61 / 54 55 56
Clutch Weight	振り子	Drive Ratio	23T Pully 384Belt 24T Pully 387Belt
Clutch Spring	VZ438(1.7)		
Clearance	0.3 mm	Rear Diff. Oil	40000
Adjust Nut	0.9 mm	Sus. Holder Spacer	Rのみ0.7mm

memo : ホイールベースはフロント側を1.5mm短くしてリア側は1ミリ伸ばす。(Rアーム後端の突起を1mmカットする)

92987C SPブレーキパッド, VZW445フルアルミニウムユニバーサルスイングシャフトセット使用

予選時のタイヤ径は59/60