

# V·ONE R4EVO.

Name	齊藤 楓真	Temp	°C	Engine	YURUGIX TG12	Muffler	YURUGIX
Date	2018/09/09	Humidity	%	Head Clearance	mm	Fuel Type	NASA
Track	グリーンパークスピードウェイ	Traction	%	Plug No.	No.4	Radio	SANWA

Shock Position  
W5308VVC  
VVC Big Bore Short Shock

Chassis Height

Down Stop

Servo Saver  
R  
E

Caster Angle (Caster Spacer)

Servo Saver  
0 0.5 1.0

Bump Steering

Wheel Base

Shock Position  
A B C D E

VZW435

Shock Oil	800	
Diaphragm	W5307-05(+W5302-02)	
Shock Piston	W5307-09 (3-1.1)	
Spring	W5307-29 (Purple)	
Spring Adjuster	mm	
Shock Position	D	
Caster Angle(Spacer)	2 mm	
Camber Angle	L	0 0.5 1 1.5 ② 2.5 3
0G/1G	R	0 0.5 1 1.5 ② 2.5 3
Toe Angle	Out 1 deg	
Front Width	197 mm	
Down Stop	-1.5 mm	
Wheel Spacer	0 mm	
Antiroll Bar	VZ084SS ⊘30deg	
Tire		
Wheel Offset	0 mm	
Tire Diameter	mm	
Chassis Height	6.5 mm	
Used Optional parts		

Weight Position	0 mm	
Servo Saver	0	
Wheel Base	Ⓝ Short	
Upper Arm Position	F ⊙ R ⊙ ⊙	
Bump Steering	0 mm	
Knuckle Type	0 deg	
Front Diff. Oil	70万(50万:100万/1:1)	

Upper Arm Spacer (Out)

W5308VVC  
VVC Big Bore Short Shock

Chassis Height

Down Stop

Upper Arm Position (In)

A B C

Wheel Spacer

Shock Position  
A B C D E

VZW436

Sus. Holder Spacer

Wheel Base

Upper Arm Position (In)  
for VZW433  
D

Shock Oil	1000	
Diaphragm	W5307-05(+W5302-02)	
Shock Piston	W5307-09 (3-1.1)	
Spring		
Shock Position	E	
Wheel Spacer	0	
Upper Arm Position (In)	D (VZW433)	
Upper Arm Spacer (Out)	1.5mm	
Camber Angle	L	0 0.5 1 1.5 2 2.5 ③ 3.5 4
0G/1G	R	0 0.5 1 1.5 2 2.5 ③ 3.5 4
Toe Angle	3 deg	
Rear Width	200 mm	
Down Stop	+1.5 mm	
Antiroll Bar	2.1 mm	
Tire		
Wheel Offset Type	0 mm	
Tire Diameter	mm	
Chassis Height	8 mm	
Lower Arm Position	⊙(ZERO) ⊙(OUT1mm)	
Weight		
Wheel Base	Ⓝ Short	
Body-Shell	SRC SPARK	

Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total				
16	61	7.63	16	60	7.50	16	59	7.38	21	56	5.33	21	55	5.24	21	54	5.14
17	61	7.18	17	60	7.06	17	59	6.94	22	56	5.09	22	55	5.00	22	54	4.90
						59			23	56	4.87	23	55	4.78	23	54	4.69

Clutch Type	VZW442	Pinion Gear	⑮ 16 17 / ⑳ 21 22 23
Clutch Shoe	VZW442	Spur Gear	59 60 ① / 54 ⑤ 56
Clutch Weight	VZW442	Drive Ratio	2.5mm Difference(23T Pully 384Belt)
Clutch Spring	VZW442		
Clearance	1.2 mm	Rear Diff. Oil	40000
Adjust Nut	0.5 mm	Sus. Holder Spacer	0.75mm (後ろ側のみ)

memo : VZW431, VZW432, VZW433, VZW437-2, VZW438, VZW439, VZW440, VZW441, 92987B 使用  
 TH-Servo PGS-LH , ST-Servo PGS-XR , Receiver Battery Muchmore INPACT 2500  
 バッテリー下に30グラム, バッテリー左横に15グラム