

ULTIMA RZ6 SET UP SHEET



Name Daisuke Sakamoto Date 17/06/04 Truck / City Yatabe Arena(Carpet) Event For 2017 Japan nationals

Front Suspension:

Shock Position:

Shock Stay: Std. UMW714 (Carbon comp) UMW733 (Carbon t=5.0)

Upper Spacer: 2 mm

Toe: In Out 1°

Tie Rod: _____

Front Bulkhead Weight Placement: None Bulkhead Inside 9 On the skid plate 9

4.8mm Ball Stud: UM128(Std.) UMW508(+2mm High Mount)

4.8mm Ball Stud Spacer: 0.5 mm

Camber: 1.5°

AL. Steering Support: None UMW724

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: 0 mm

Ackerman arrow direction: Front(std) Rear

Option: UMW701 Alu ST Plate UMW702 Alu Clank Arm

Bump Steer Spacer: 0 mm

Wheel Hub: UM569 / Std UM506

Axle Spacer: Out _____ mm In 3 mm

Caster: 25° 30° A (UM502) B (UM721/Std) B (UMW722/Brass) B (UMW723/Alu) C (UM567)

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Caster Block Position: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: 1.5 mm 0 mm

Wheelbase: F: 0 mm R: 1 mm

Comments: **Hub carrier is shaved (削る)**

Rear Suspension:

Shock Position:

Wing Stay Position:

Shock Stay Type: LA352(std) LAW59 (Carbon/2mmLow)

Lower Sus Holder Block: Front in C Rear out E

Lower Sus Holder Spacer: Front 0.5 mm Rear 0.5 mm

Comments: _____

Upper Arm Position:

4.8mm Ball Stud: 97050M(Std) UM129

Upper Spacer: 0 mm

Camber: 2°

Sus.Arm: LA272(std) UM713B UMW711B

Hub Carrier:

Type-B (UM519) Type-B2 (UM519-2)

0°Type-B(UM519) 0°Type-B2(UM519-2) 0°Alu(UMW704-0) 0.5°Alu(UMW704-05) 1°Alu(UMW704-1)

Wheelbase: Front: 2 mm 2 mm 2 mm Rear: 0 mm

Sway Bar: None 1.4 mm 0 mm

Rear Diff: Gear Diff. (Oil:# 10000) (Oil weight: 1.5 g) Ball Diff.

Shock:

Shock Piston:	Front <u>2x1.7</u>	Rear <u>2x1.7</u>
Shock Oil:	# <u>600</u>	# <u>500</u>
Shock Spring:	<u>Red</u>	<u>Gold</u>
Limiters:	in _____ mm out <u>0</u> mm	in _____ mm out <u>0</u> mm
Shock Length(A):	<u>20</u> mm	<u>26.5</u> mm
Shock Top Type:	<input checked="" type="checkbox"/> Alu(UM719/Std) <input type="checkbox"/> UM753-1	

5.8mm Ball End:

Front:	<input type="checkbox"/> S <input type="checkbox"/> M <input checked="" type="checkbox"/> L
Rear:	<input type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L

Chassis:

Ride Height:

Front 15 mm Rear A B 15 mm

Tire:

Front	Rear
Tire: <u>YAU-6770</u>	<u>YAU-6826</u>
Inserts: <u>None</u>	<u>YAU-6734</u>
Wheel: <u>W5029W width 20mm</u>	<u>W5202W</u>
Traction Compound:	

Electronics:

Battery: 1S size Saddle Pack Short

Battery Position: Std 8mm Front

Motor Position: Front Rear

Motor Mount Position: Std 8mm Front

Motor: ORION VST2 LW 5.5T

Pinion/Spur: 19 / 76

Body / Wing:

Body: UMB04LW

Wing Mount: Narrow Wide

Wing Dum Height: 20.5 mm

Wing: PL Champion 6.5

Wing Angle: 4° 7° 10°

Lip Height: 11 mm

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear

Comment : RB6 Front wing (6283-01)612174

LAW55 Rear Center Plate LAW53 Carbon Composite Rear Stiffener

UMW710&711B Carbon Composite Front&Rear Sus.Arm

UMW712 & 713 Carbon Composite Front Knuckle & Front hub carrer