

LAZER ZX7 SET UP SHEET



Name Kohta Akimoto Date 19/7/7 Truck / City RC PARK GOJO Japan National Championship Qual 5th • Final 6th

Front Suspension:

Shock Position: ① ② ③ ④

Shock Stay:
 Std.
 Carbon (LAW58)
 Other Low down type LAW70

Lower Sus Holder Block:
 Front Out_D Rear Out_D

Lower Sus Holder Spacer:
 Front 0.5 mm Rear 0.5 mm

Upper Arm Position: ① ② ③

4.8mm Ball Stud:
 UM129(Std)
 97050M

Upper Spacer: 1 mm

Camber: 1.5 °

Spacer: 1 mm

Shock Position: ① ② ③

Wheelbase: Front 1 mm Rear 1 mm

Bump Steer Spacer: 1 mm

Toe:
 In
 Out 1 °

Sway Bar:
 None
 mm

Axle-Height Spacer:
 Up
 Down

Caster Block:
 7° 13°
 10°

Sus. Bush:
 Wide
 Narrow(Std)

Ackerman Spacer: 2 mm

Front Diff:
 Gear Diff. # 5,000
 Ball Diff.

Comments:

Rear Suspension:

Shock Position: ① ② ③ ④

Shock Stay:
 Std.
 Carbon (LAW59)
 Other

Wing Stay Position:

Lower Sus Holder Block: Toe In: Front OUT_B Rear OUT_B 3.0

Lower Sus Holder Spacer:
 Front 0.5 mm Rear 0.5 mm

Upper Arm Position: ① ② ③

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: 1 mm

Sus. Arm:
 LA272
 UM713B
 UM762(Std)

Camber: 1.5 °

Hub Carrier: ① ② ③ ④
 Type-B (UM519)
 Type-B2 (UM519-2)
 0°Alu(UMW704-0)
 0.5°Alu(UMW704-05)
 1°Alu(UMW704-1)

Upper Spacer: 2 mm

Shaved hub

Sus. Bush:
 IN OUT (Std.)

Wheelbase: Front 2 mm Rear 0 mm

Axle Spacer:
 Out 0 mm
 In 2.3 mm

Wheelbase: Front: 1 mm Rear: 3 mm

Sway Bar:
 None
 1.1 mm
 4.5mm (LAW30GM/Std.)

Center Drive:
 Diff. Gear Slipper Clutch
 #

Rear Diff:
 Gear Diff. # 5,000
 Ball Diff.

Comments:

Shock:

	Front	Rear
Shock Piston:	<u>2x1.6</u>	<u>2x1.7</u>
Shock Oil:	# <u>550</u>	# <u>500</u>
Shock Spring:	<u>Gold</u>	<u>Gold</u>
Limiters:	in <u>0</u> mm out <u>0</u> mm	in <u>0</u> mm out <u>0</u> mm
Shock Length (A):	<u>21.0</u> mm	<u>28.5</u> mm
Shock Top Type:	<input type="checkbox"/> Alu. (UM719) <input checked="" type="checkbox"/> UM753-1B(Std.)	
Ball End:	Front: S <input type="checkbox"/> M <input checked="" type="checkbox"/> L Rear: S <input type="checkbox"/> M <input checked="" type="checkbox"/> L	Spring Sheet: Front: <input checked="" type="checkbox"/> Rear: <input checked="" type="checkbox"/>

Shock (A): A

Chassis:

Center Bulk:
 Front Rear (Std.)

Ride Height: Front 16.5 mm Rear 16.5 mm

Electronics:

Motor: ORION ULTIMATE 6.5T

Pinion / Spur: 20/78

ESC: ORION HMX 10

Radio: FUTABA 7PX

Servo: OS T-1 SR1

Battery: ORION 4000 LCG

Tire:

	Front	Rear
Tire:	<u>PL-Positron</u>	<u>PL-Positron</u>
Compound:	<u>MC</u>	<u>MC</u>
Inserts:	<u>Std</u>	<u>Std</u>
Wheel:	<u>Std</u>	<u>Std</u>

Note:

Body / Wing:

Body: LAB07LW (t0.6)

Wing Dum Height: 20 mm

Wing: UM767

Wing Angle: 4° 7° 10°

Lip Height: 15 mm

Comment:

LAW71 Carbon Front Brace
 LAW72 Carbon Rear Brace
 LAW75 Titanium Screw Set

New!
 LAW76 Aluminum Center Shaft (68.5/7075)
 LAW78 Aluminum Center Shaft (77.5/7075)

Truck Condition

<input checked="" type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Truction	<input type="checkbox"/> Grass
<input checked="" type="checkbox"/> Med. Truction	<input type="checkbox"/> Blue Groore
<input type="checkbox"/> Higt Truction	<input checked="" type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> <u> </u>

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminum

Shock O-Ring: O-ring X-ring Red Clear