

Name: Mio Hakamada Date: 17/11/26 Truck/city: Yatabe arena Event: AOC Rd5

### Front Suspension

**Shock Stay Type :** ☒ King Pin ☐ 97040(Low) ☐ UM128(std.)

**Upper Spacer :** ☒ TFW172(std.) ☐ 0.5 mm

**Upper End :** ☒ UM112H(std.) ☐ UM112

**Hub Carrier Type :** ☒ 4°(TF225H/std.) ☐ 6°(TF225-6H)

**Knuckle Spacer :** ☒ Upper ☐ Lower

**Wheel Spacer :** ☒ 0 mm

**Knuckle :** ☒ TF243(TF7/Std.) ☐ TF237(TF6SP)

**Drop :** ☒ A ☐ B 5.8 mm

**Sus Arm :** ☐ TF268-01B(L) ☒ TF279-01B(M/Std.) ☐ TF280(S)

**Sus.Holder Type :** ☒ TF212(Separates/std.) ☐ TFW120(Onepiece)

**Drive Hub :** ☐ TFW113(4.0/std.) ☒ LAW30R(4.5) ☐ TFW031(5.2)

**Ride Height :** 5.1 mm

**ST Servo Horn :** ☐ Plastic(IF435/Std.) ☐ Aluminum (IFW448/F) (IFW449/S/K)

**Sus. Arm Spacer :** Front: 2 mm Rear: 1 mm

**Clank Bridge :** ☐ Use ☒ No Use

**Knuckle Spacer :** 1 mm

**RC MISSION 18.5mm**

**Diff. Position :** ☐ ☒ 13.5mm

**Spool Cup :** ☐ TFW124(Alu.) ☒ TF287(Steel / std.)

**Swing Shaft :** ☒ TF272(Std./TFW121) ☐ TFW122(40.5mm)

**Sus.Holder Bush :** Front: In / Out F 0 mm Rear: In / Out F 0 mm

**Sus. Holder Spacer :** 0 mm

**Sway Bar Holder :** ☐ Plastic(TF269/Std./Cut) ☒ Plastic(TF269/Std./No Cut) ☐ Aluminum(TFW110)

**Camber Angle :** 1.5°

**Sway Bar :** 1.3 13.5mm

**Toe Angle :** ☐ IN ☒ Out 1°

**Front Diff :** ☒ Spool ☐ C-joint ☐ Pin ☐ One Way ☐ Gear Diff (Oil:# ) (Oil Weight: g)

### Rear Suspension

**Shock Stay Type :** ☒ TFW173(std.) ☐ UM112H(std.) ☐ UM112

**Upper Spacer :** ☒ 0.5 mm

**Upper End :** ☒ UM112H(std.) ☐ UM112

**Hub Carrier :** ☐ 0°(TF225-0H) ☐ 4°(TF225H)

**Knuckle Spacer :** ☐ Upper ☐ Lower

**Sus Arm Spacer :** Front: 1.5 mm Rear: 1.5 mm

**Sus. Holder :** ☒ TF266(std.) ☐ TF131

**Motor Height :** ☐ Up ☒ Low

**Ride Height :** 5.3 mm

**Camber Angle :** 2°

**Toe Angle :** 2.5°

**Swing Shaft :** ☐ TFW032-01B(46) ☒ TF007-01(43)

**Drop :** ☐ A ☐ B 4.5 mm

**Sus. Arm :** ☒ TF268-02(L/Std.) ☐ TF279-02(M) ☐ TF280(S)

**Sus.Holder Type (F):** ☐ TF286(Separates/std.) ☒ TF212(Separates) ☐ TFW120(Onepiece)

**Sway Bar Holder :** ☐ Plastic(TF269/Std./Cut) ☒ Plastic(TF269/Std./No Cut) ☐ Aluminum(TFW110)

**Camber Angle :** 2°

**Toe Angle :** 2.5°

**Rear Diff :** ☒ Gear Diff(Oil:# 7000) (Oil Weight: 1.5 g) ☐ Ball Diff

**Sus. Holder Bush :** Front: In / Out B 0 mm Rear: In / Out A 0 mm

**Sus. Holder Spacer :** 0 mm

**Wheel Spacer :** 0 mm

**Drive Hub :** ☐ TFW113(4.0/std.) ☒ LAW30R(4.5) ☐ TFW031(5.2)

**Upper Rod Position :** ☐ Spacer / Outside: mm ☐ Spacer / Inside: mm

**A.R.T.S. :** ☐ 0°(TF225-0H) ☐ 4°(TF225H)

### Shock

**Hole** 1mm

|                 | Front                                                                     | Rear                     |
|-----------------|---------------------------------------------------------------------------|--------------------------|
| Shock Piston :  | <u>4 - 1.1</u>                                                            | <u>4 - 1.1</u>           |
| Shock Oil :     | # <u>KY500</u>                                                            | # <u>KY500</u>           |
| Shock Spring :  | <u>Red(2.7)</u>                                                           | <u>Red(2.7)</u>          |
| Diaphragm :     | <u>std</u>                                                                | <u>std</u>               |
| Pressure Form : | <u>None</u>                                                               | <u>None</u>              |
| Shock Length :  | <u>9.5</u> mm                                                             | <u>9.5</u> mm            |
| Outer Spacer :  | <u>0</u> mm                                                               | <u>0</u> mm              |
| Shock Type :    | <input checked="" type="checkbox"/> W5307R(Std.) <input type="checkbox"/> | <input type="checkbox"/> |

### Steering Wiper

**Steering Spacer :** 2 mm

### Chassis

**Top Deck Screw :** ☐ Steel(Std.) ☒ Titanium ☐ Aluminum

**Weight :** 5 g

**Chassis Screws :** ☐ Front ☐ Rear

**Battery Position :** ☐ Front ☐ Rear

**Weight :** 5 g

**Center Stiffner :** ☒ Use ☐ No Use

**Weight :** 20 g

**Belt Tensioner :** ☒ TFW174

**Chassis :** ☐ Carbon(TF281/std.) ☒ Aluminum (TFW177R/TFW177BK)

### Tire

**Tire** SWEEP AOC Control

**Inserts** \_\_\_\_\_

**Wheel** \_\_\_\_\_

**Traction Compound** 1st: TC2 2nd: \_\_\_\_\_

### Comments

### Others

**Motor** Yokomo 13.5T

**Pinion/Spur** \_\_\_\_\_ / \_\_\_\_\_ **Gear Ratio** \_\_\_\_\_

**Battery** XENON 5200 **ESC** HOBBY WING

**Body** LTC-R pro light **Wing** LTC-R LW

**2nd Gear Ratio :** 1.90

### Track Condition

☐ Smooth ☐ Asphalt

☐ Bumpy ☐ Concrete

☐ Low Traction ☒ Carpet

☐ Med Traction ☒ Indoor

☒ High Traction ☐ Outdoor

### Comment :

Shock O-ring use ORG03XR (Red)