

V·ONE R4Evo. ラバータイヤ仕様

V-ONE R4 Evo. SETTING DATA Ver 1.00

Name	Miyazaki	Temp	°C	Engine	GXR-15V	Muffler	39064 (φ7)
Date	2015.12.14	Humidity	%	Head Clearance	mm	Fuel Type	R246 30%
Track	SRT	Traction	%	Plug No.		Radio	Kyosho KT-432PT

Shock Position A B C D

Spring Adjuster

Wheel Spacer

Chassis Height

Down Stop

Wheel Base

Caster Angle (Caster Spacer)

Servo Saver 0 0.5 1.0

Weight Position	一番後ろ
Servo Saver	0.5を逆向きで使用
Wheel Base	Ⓝ Short
Upper Arm Position	前 Ⓞ 後 Ⓞ
Bump Steering	+ 1 mm
Knuckle Type	Ⓞ deg 1 deg 2 deg
Front Diff. Oil	#300000

Shock Oil	300 350 400 450 500 550 600 700 800
Diaphragm	W5189-05+W5189-06
Shock Piston	Ⓝ
Spring	W5189-28B (ピンク)
Spring Adjuster	車高に合わせる
Shock Position	A B C Ⓞ
Caster Angle(Spacer)	1 mm
Camber Angle	L 0 0.5 1 1.5 2 2.5 3 0G 1G R 0 0.5 1 1.5 2 2.5 3
Toe Angle	片側out0.5 deg
Front Width	200 mm
Down Stop	-1 mm
Wheel Spacer	1 mm
Antiroll Bar	なし
Tire	KC-M or KC-H
Wheel Offset	
Tire Diameter	
Chassis Height	5.0 mm
Used Optional parts	

Shock Position A/B/C/D/E/F/G/H/I

Upper Arm Position

Wheel Spacer

Chassis Height

Down Stop

Weight Position

Rear

Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total
16	61	7.63	16	60	7.50	16	59	7.38	21	56	5.33
17	61	7.18	17	60	7.06	17	59	6.94	22	56	5.09
							59		23	56	4.87
									23	55	5.24
									22	55	5.00
									22	54	4.90
									23	54	4.69

Shock Oil	300 350 400 450 500 550 600 700 800
Diaphragm	W5189-05+W5189-06
Shock Piston	Ⓝ
Spring	W5189-34 (ブルー)
Spring Adjuster	車高に合わせる
Shock Position	A/B/C Ⓞ E/F/G/H/I
Wheel Spacer	1 mm
Upper Arm Position	外側に1mm、memo参照
Camber Angle	L 0 0.5 1 1.5 2 2.5 3 3.5 4 0G 1G R 0 0.5 1 1.5 2 2.5 3 3.5 4
Toe Angle	片側in2.5 deg
Rear Width	200 mm
Down Stop	0 mm
Antiroll Bar	なし mm
Tire	KC-M or KC-H
Wheel Offset Type	
Tire Diameter	

Clutch Type	VZ457 アルミ	Pinion Gear	15 16 17 / 20 21 22 23	Chassis Height	5.3 mm
Clutch Shoe		Spur Gear	59 60 61 / 54 55 56	Lower Arm Position	Ⓞ(ZERO) Ⓞ(OUT1mm) N / UP mm
Clutch Weight		Drive Ratio	0mm Difference(24T Pulley 387Belt) 2.5mm Difference(23T Pulley 384Belt)	Weight	
Clutch Spring		Rear Diff. Oil	#7000	Wheel Base	Ⓝ Short
Clearance		Sus. Holder Spacer	2 mm	Body-Shell	SC430 (new)
Adjust Nut					

memo : ※1: アッパーアーム内側はVZW425のこの穴を使用
・ダンパーはシャフトを伸ばした状態で組立て