

V·ONE R4Evo.

V-ONE R4 Evo. SETTING DATA Ver 1.00

Name	Temp	°C	Engine	Muffler
Date	Humidity	%	Head Clearance	mm
Track	Traction	%	Plug No.	Radio

Shock Position	A	B	C	D
Weight Position	mm			
Servo Saver	0	0.5	1.0	
Wheel Base	N	Short		
Upper Arm Position	⊙	⊙	⊙	
Bump Steering	N	mm		
Knuckle Type	0 deg	1 deg	2 deg	
Front Diff. Oil				

Shock Oil	300 350 400 450 500 550 600 700 800
Diaphragm	N
Shock Piston	N
Spring	
Spring Adjuster	mm
Shock Position	A B C D
Caster Angle(Spacer)	mm
Camber Angle	L 0 0.5 1 1.5 2 2.5 3 0G/1G R 0 0.5 1 1.5 2 2.5 3
Toe Angle	deg
Front Width	mm
Down Stop	mm
Wheel Spacer	mm
Antiroll Bar	(N)VZ084S VZ084SS VZ084 <input type="radio"/>
Tire	
Wheel Offset	mm
Tire Diameter	mm
Chassis Height	mm
Used Optional parts	

Shock Position	A/B/C/D/E/F/G/H/I
Weight Position	mm
Upper Arm Position	⊙
Down Stop	mm
Chassis Height	mm
Wheel Spacer	mm
Upper Arm Position	mm A / B / C / D VZW425
Camber Angle	L 0 0.5 1 1.5 2 2.5 3 3.5 4 0G/1G R 0 0.5 1 1.5 2 2.5 3 3.5 4
Toe Angle	deg
Rear Width	mm
Down Stop	mm
Antiroll Bar	N
Tire	
Wheel Offset Type	mm
Tire Diameter	mm
Chassis Height	mm
Lower Arm Position	⊙(ZERO) ⊙(OUT1mm) N / UP mm
Weight	mm
Wheel Base	N Short
Body-Shell	

Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total
16	61	7.63	16	60	7.50	16	59	7.38	21	56	5.33
17	61	7.18	17	60	7.06	17	59	6.94	22	56	5.09
							59		23	56	4.87
									23	55	4.78
									23	54	4.69

Shock Oil	300 350 400 450 500 550 600 700 800
Diaphragm	N
Shock Piston	N
Spring	
Spring Adjuster	mm
Shock Position	A/B/C/D/E/F/G/H/I
Wheel Spacer	
Upper Arm Position	mm A / B / C / D VZW425
Camber Angle	L 0 0.5 1 1.5 2 2.5 3 3.5 4 0G/1G R 0 0.5 1 1.5 2 2.5 3 3.5 4
Toe Angle	deg
Rear Width	mm
Down Stop	mm
Antiroll Bar	N
Tire	
Wheel Offset Type	mm
Tire Diameter	mm
Chassis Height	mm
Lower Arm Position	⊙(ZERO) ⊙(OUT1mm) N / UP mm
Weight	mm
Wheel Base	N Short
Body-Shell	

Clutch Type	N ()	Pinion Gear	15 16 17 / 20 21 22 23
Clutch Shoe	N ()	Spur Gear	59 60 61 / 54 55 56
Clutch Weight	N / Other ()	Drive Ratio	0mm Difference(24T Pully 387Belt)
Clutch Spring	N (φ1.7) / VZ446 (φ1.8)		2.5mm Difference(23T Pully 384Belt)
Clearance	mm	Rear Diff. Oil	
Adjust Nut	mm	Sus. Holder Spacer	mm

memo :

