

Name	下高章	Temp	℃	Engine	12XZ SPEC II Proto	Muffler	T-1060
Date	2012/6/24	Humidity	%	Head Clearance	mm	Fuel Type	コスモ 16%
Track	O.S.Field	Traction	%	Plug No.	RP6	Radio	フタバ

	Shock Position	A B C D
	Shock Oil	300 350 400 450 500 550 600 700 800
	Diaphragm	Ⓐ
	Shock Piston	Ⓐ
	Spring	Red
	Spring Adjuster	mm
	Shock Position	Ⓐ B C D
	Caster Angle (Spacer)	3 mm
	Camber Angle	L 0 0.5 ① 1.5 2 2.5 3
	OG1G R	0 0.5 ① 1.5 2 2.5 3
	Toe Angle	-1 deg
	Front Width	199.5 mm
	Down Stop	-1 mm
	Wheel Spacer	0 mm
	Antiroll Bar	VZ084SS Super Soft / VZ084S Soft / Sway(φ) Bar
	Tire	ZBB-811cch / deg
	Wheel Offset Type	mm
	Tire Diameter	φ 63 mm
	Chassis Height	7.5 mm
	Servo Saver	0 0.5 ①+1.0
	Wheel Base	Ⓐ Short
	Upper Arm Position	Ⓐ ② ③
	Bump Steering	Ⓐ FM624
	Knuckle Type	① deg 1 deg 2 deg
	Front Diff Oil	300000

	Shock Position	A/B/C/D/E/F/G/H/I
	Shock Oil	300 350 400 450 500 550 600 700 800
	Diaphragm	Ⓐ
	Shock Piston	Ⓐ
	Spring	Yellow
	Spring Adjuster	mm
	Shock Position	A ① B C/D/E/F/G/H/I
	Wheel Spacer	0 mm
	Upper Arm Position	2 mm A ① B C
	Camber Angle	L 0 0.5 ① 1.5 2 2.5 3 3.5 4
	OG1G R	0 0.5 ① 1.5 2 2.5 3 3.5 4
	Toe Angle	+3 deg
	Rear Width	199.5 mm
	Down Stop	0 mm
	Antiroll Bar	Ⓐ mm
	Tire	ZBB-9121ch / deg
	Wheel Offset Type	mm
	Tire Diameter	φ 65 mm
	Chassis Height	8.5 mm
	Lower Arm Position	Ⓐ (ZERO) ② (OUT 1mm)
	Weight	Ⓐ / UP mm
	Wheel Base	Ⓐ Short
	Body-Shell	

Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total
16 61	7.63	16 60	7.50	16 59	7.38	21 56	5.33	21 55	5.24	21 54	5.14
17 61	7.18	17 60	7.06	17 59	6.94	22 56	5.09	22 55	5.00	22 54	4.90
				59		23 56	4.87	23 55	4.78	23 54	4.69

Clutch Type	Ⓐ (N/ZW229)	Pinion Gear	(15) 16 ① (20) 21 ② 23
Clutch Shoe	Grey / Other (Yellow)	Spur Gear	59 60 ① / 54 ⑤ 56
Clutch Weight	Ⓐ Other ()	Drive Ratio	0mm Difference (24T Pully 387Belt)
Clutch Spring	Ⓐ (1.7) 1.8		2.5mm Difference (23T Pully 384Belt)
Clearance	0.7 mm	Rear Diff Oil	50000
Adjust Nut	1.3 mm	Battery Plate	N (Carbon) / Other ()

Memo OP シャシー

F, R デフの上 アルミ

F ボディマウント 外側