

Name	下高章	Temp	℃	Engine	12XZ SPEC III	Muffler	OST-1060
Date	2012/9/9	Humidity	%	Head Clearance	mm	Fuel Type	コスモ 16%
Track	ホクセイサーキット	Traction	%	Plug No.	RP6	Radio	フタバ4PKSR

				Shock Oil	300 350 400 450 500 550 600 700 800
				Diaphragm	Ⓝ
				Shock Piston	Ⓝ
				Spring	BLUE
				Spring Adjuster	mm
				Shock Position	Ⓐ B C D
				Caster Angle (Spacer)	3 mm
				Camber Angle (G1G)	L 0 0.5 ① 1.5 2 2.5 3 R 0 0.5 ① 1.5 2 2.5 3
				Toe Angle	-1.5 deg
				Front Width	199 mm
				Down Stop	0 mm
				Wheel Spacer	0 mm
				Antiroll Bar	VZ084SS Super Soft / VZ084S Soft Sway(φ) Bar mm
				Tire	ZBB-812CSH / deg
				Wheel Offset Type	mm
				Tire Diameter	φ 63 mm
				Chassis Height	8 mm
				Servo Saver	0 0.5 ①1.0
				Wheel Base	Ⓝ Short
				Upper Arm Position	ⓐ ⓑ ⓒ
				Bump Steering	N FM624
				Knuckle Type	ⓐ deg 1 deg 2 deg
				Front Diff Oil	500000
				Shock Oil	300 350 400 450 500 550 600 700 800
				Diaphragm	Ⓝ
				Shock Piston	Ⓝ
				Spring	BLUE
				Spring Adjuster	mm
				Shock Position	A ⓑ C/D/E/F/G/H/I
				Wheel Spacer	0 mm
				Upper Arm Position	2 mm ⓓ A/B/C
				Camber Angle (G1G)	L 0 0.5 1 ①.5 2 2.5 3 3.5 4 R 0 0.5 1 ①.5 2 2.5 3 3.5 4
				Toe Angle	+3 deg
				Rear Width	199.5 mm
				Down Stop	-1 mm
				Antiroll Bar	Ⓝ 2 mm 2.0→2.1
				Tire	ZBB-9121SH / deg
				Wheel Offset Type	mm
				Tire Diameter	φ 65 mm
				Chassis Height	9 mm
				Lower Arm Position	ⓐ (ZERO) ⓑ (OUT 1mm) ⓓ / UP mm
				Weight	L(A ⓑ ⓒ ⓓ) R/Rear
				Wheel Base	Ⓝ Short
				Body-Shell	P-37N
				Clutch Type	Ⓝ (ZW229)
				Pinion Gear	(15) 16 ①7 / (20) 21 ②2 23
				Clutch Shoe	Grey / Other(Yellow)
				Spur Gear	59 60 ⓐ1 / ⓑ4 55 56
				Clutch Weight	Ⓝ Other()
				Drive Ratio	0mm Difference(24T Pully 387Belt) ②.5mm Difference (23T Pully 384Belt)
				Clutch Spring	Ⓝ (1.7) 1.8
				Clearance	0.7 mm
				Rear Diff Oil	40000
				Adjust Nut	1.4 mm
				Battery Plate	N(Carbon) / Other()
				Memo	OP シャシー フロントバンパー固定 リヤデフの上アルミ リヤユニバーサル アルミ F ボディマウント 内側

Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total	Gear	Total
16 61	7.63	16 60	7.50	16 59	7.38	21 56	5.33	21 55	5.24	21 54	5.14
17 61	7.18	17 60	7.06	17 59	6.94	22 56	5.09	22 55	5.00	22 54	4.90
				59		23 56	4.87	23 55	4.78	23 54	4.69

Clutch Type	Ⓝ (ZW229)	Pinion Gear	(15) 16 ①7 / (20) 21 ②2 23
Clutch Shoe	Grey / Other(Yellow)	Spur Gear	59 60 ⓐ1 / ⓑ4 55 56
Clutch Weight	Ⓝ Other()	Drive Ratio	0mm Difference(24T Pully 387Belt) ②.5mm Difference (23T Pully 384Belt)
Clutch Spring	Ⓝ (1.7) 1.8		
Clearance	0.7 mm	Rear Diff Oil	40000
Adjust Nut	1.4 mm	Battery Plate	N(Carbon) / Other()

Memo OP シャシー フロントバンパー固定 リヤデフの上アルミ リヤユニバーサル アルミ F ボディマウント 内側