

Driver	Date	Event	Track / CITY	Body	Transmitter
Kyosho Works Driver Kuniaki Noguchi	2010/7/18	Shop Meeting	MANISPO	ENZO	EX-10 EURUS

Tick the boxes where appropriate, and fill in blanks with values.

Track Condition	Battery
Carpet - <u>Urethane</u>	Alkaline Dry Battery()
Other ()	<u>NiMH Battery</u> (ORION 750SHO)
	Other()

● Chassis type

- Standard (Black)
 SP (Gray)
 Translucent

● Motor

- Standard
 XSPEED V
 Pinion gear
 9T 8T
 7T 6T

● Rear Shock

- Spring Soft (Red)
 Standard (Green)
 Hard (Yellow)
 Other ()

- Standard Oil Shock

Oil No. 200
 Spacer 0 mm

Friction Shock

- Carbon Plastic (for LM)
 Friction Plate Upper Lower

● Suspension Plate(T-bar)

- Standard
 Carbon FRP
 Type
 Soft
 Medium
 Hard

Height adjustment spacers

0.2mm x _____ pcs

● Suspension Plate Guide

- Standard
 Option

● Gyro Unit

- Installed

● Motor Mount

- HM MM
 RM LM
 RML

● Wheel Base

- S M L LL 3L

● Differential

- Gear Diff.
 Ball Diff.


Diff. Ball

- Standard
 Ceramic

Axle

- Standard
 Titanium

● Front Suspension



Spring

- Soft(Red) Medium Soft(Purple)
 Medium(Green)
 Medium Hard(Orange/Standard)
 Hard(Yellow)

Suspension Limiter

- A 1.75 mm
 B 0 mm
 C 1 mm

Upper Suspension Arm

- Standard
 Inner Tube
 Aluminum

King Pin Ball

- Standard
 SP Long

4.7mm Ball

- Standard
 Hard Fluorine Coat

Upper Suspension Shaft

- Standard SP

● Tie-Rod

- 2°
 Standard-0°
 +2°
 +4°
 +6°

● Front Tire

- Narrow Semi Wide Wide
 High Grip Flat
 Classic LM
 Racing Radial
 Hardness 30° Diameter 23.5 mm

● Front Wheel

- (Fill in one of the following)
 Part No. _____
 Offset 1 mm
 Chassis width at front wheels _____ mm

● Screw

- Standard
 Color
 Titanium

● Rear Tire

- Narrow Semi Wide Wide
 High Grip Flat
 Classic LM
 Racing Radial
 Hardness 30° Diameter 24.5 mm

● Rear Wheel

- (Fill in one of the following)
 Part No. _____
 Offset 1 mm
 Chassis width at rear wheels _____ mm

● Ball Bearing

- Installed

● Other parts installed

- MZN50-4 Front Bumper Set
MZW414 Cir Clip & Spacer Set
R246-1231 Ball Diff. Plate

● Note

- MZW413 Hard Fluorine Coat 4.7mm Ball
 (Use as Shock Ball)

