

Driver	Date	Event	Track / CITY	Body	Transmitter
Kyosho Works Driver Kuniaki Noguchi	2010/7/18	Shop Meeting	MANISPO	NISSAN GT-R R35	EX-10 EURUS

Tick the boxes where appropriate, and fill in blanks with values.

Track Condition	Battery
Carpet - <u>Urethane</u>	Alkaline Dry Battery( ) <u>NiMH Battery</u> (ORION 750SHO)
Other ( )	Other( )

● Chassis type

- Standard (Black)  
 SP (Gray)  
 Translucent

● Motor

- Standard  
 XSPEED V  
 Pinion gear  
 9T  8T  
 7T  6T

● Rear Shock

- Spring  Soft (Red)  
 Standard (Green)  
 Hard (Yellow)  
 Other ( )

- Standard  Oil Shock  
 Oil No. 200  
 Spacer 0 mm

- Friction Shock  
 Carbon  Plastic (for LM)  
 Friction Plate  Upper  Lower

● Suspension Plate(T-bar)

- Standard  
 Carbon  FRP  
 Type  
 Soft  
 Medium  
 Hard

● Height adjustment spacers

0.2mm x \_\_\_\_\_ pcs

● Suspension Plate Guide

- Standard  
 Option

● Gyro Unit

- Installed

● Motor Mount

- HM  MM  
 RM  LM  
 RML

● Wheel Base

- S  M  L  LL  3L

● Differential

- Gear Diff.  
 Ball Diff.


○ Diff. Ball

- Standard  
 Ceramic

○ Axle

- Standard  
 Titanium

● Front Suspension



○ Spring

- Soft(Red)  Medium Soft(Purple)  
 Medium(Green)  
 Medium Hard(Orange/Standard)  
 Hard(Yellow)

○ Suspension Limiter

- A 1.75 mm  
 B 0 mm  
 C 1 mm

○ Upper Suspension Arm

- Standard  
 Inner Tube  
 Aluminum

○ King Pin Ball

- Standard  
 SP  Long

○ 4.7mm Ball

- Standard  
 Hard Fluorine Coat

○ Upper Suspension Shaft

- Standard  SP

● Tie-Rod

- 2°  
 Standard-0°  
 +2°  
 +4°  
 +6°

● Front Tire

- Narrow  Semi Wide  Wide  
 High Grip  Flat  
 Classic  LM  
 Racing Radial  
 Hardness 20° Diameter 23.7 mm

● Front Wheel

- (Fill in one of the following)  
 Part No. \_\_\_\_\_  
 Offset 1.5 mm  
 Chassis width at front wheels \_\_\_\_\_ mm

● Rear Tire

- Narrow  Semi Wide  Wide  
 High Grip  Flat  
 Classic  LM  
 Racing Radial  
 Hardness 30° Diameter 24.5 mm

● Rear Wheel

- (Fill in one of the following)  
 Part No. \_\_\_\_\_  
 Offset 0 mm  
 Chassis width at rear wheels \_\_\_\_\_ mm

● Screw

- Standard  
 Color  
 Titanium

● Ball Bearing

- Installed

● Other parts installed

- MZW414 Cir Clip & Spacer Set  
R246-1231 Ball Diff. Plate

● Note

- MZW413 Hard Fluorine Coat 4.7mm Ball  
 (Use as Shock Ball)

