

# ULTIMA RB5 SP SET UP SHEET



Name  
Kohta Akimoto

Date  
2011

Truck / City  
YATABE ARENA

Event  
B.B shock set up

## Front Suspension

**Upper Spacer** 2.0 mm

**Shock Stay**  
 Std(UM511)  
 C-Comp(UMW500)

**Ball Stud**  
 Standard(UM128)  
 High Mount (+2mm:UMW508)

**Axle Type**  
 Standard(Steel:UM506)  
 Option(Aluminum:UMW507)

**Ackerman Steer Spacer** 0 mm

**Bump Steer Spacer** 0 mm

**Axle Spacer**  
 Out(Standard) \_\_\_\_\_ mm  
 In 1 mm

**Axle Height Spacer**  
 Up \_\_\_\_\_ mm  
 Down \_\_\_\_\_ mm

**Camber**  +  - 1°

**Caster**  
 25°  0.5  
 30°  1.0  
 None  None

**Toe**  In  Out 0°

**Front Bulkhead Weight Placement**  
 None  
 Bulkhead Inside \_\_\_\_\_ oz 10 g \* 1oz=28g  
 On the skid plate \_\_\_\_\_ oz 5 g

Comments:

## Rear Suspension

**Lower Sus Holder**  
 Normal  RF:RB5  Aluminum(Opt) UMW511+UMW512  
 Wide  RF2:RB5SP  UMW514+UMW515

**Upper Spacer** 3.0 mm

**Wing Height**  
 1  
 2  
 3

**Sus Holder Spacer**  
 F  0.5  1.0  None  
 R  0.5  1.0  None

**Anti-Squat** \_\_\_\_\_°

**Swing Shaft**  
 62.5mm:RB5(UM510,UM510-01)  
 65.5mm:RB5SP(UM522,LA232-01)

**Lower Arm**  
 Short:RB5(UM503)  
 Middle:RB5SP(UM521)

**Wheelbase**  
 Long  
 Middle  
 Short

**Rear Hub add Toe**  
 0° (Standard)  
 0.5° (LA244-05)

**Sway Bar**  None  \_\_\_\_\_ mm

**Axle Spacer**  
 Out \_\_\_\_\_ mm  
 In 0.3 mm

**Wheel Shaft Type**  
 RB5SP(UM522-02)  
 RB5(UM510-02)  
 Type-B(UM519)  
 Up(LA244-05)  
 Middle  
 Down  
 Type-B2

**Wheel Spacer** \_\_\_\_\_ mm

Comments:

**Shock**

	Front	Rear
Shock Piston	Std -	Std -
Shock Oil	# 30 (Xgear RED)	# 25 (Xgear RED)
Shock Spring	White	White
Limiters	in out mm mm	in out mm mm
Shock Length(A)	_____ mm	_____ mm
Shaft Length(B)	20.0 mm	28.5 mm
Shock Top Type	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
Rear Shock Body	<input checked="" type="checkbox"/> Short:RB5SP(W5196-01V) 38mm <input type="checkbox"/> STD:RB5(W5187-01V) 42mm	<input checked="" type="checkbox"/> STD:RB5SP(W5193-01) 50mm <input type="checkbox"/> Opt:ZX5(W5183-02) 54mm

Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS

**Body / Wing / Chassis**

**Wing**  
 Aquarius(LA239)  
 Sagittarius(LA240)  
 Aries(LA241)  
 Blast-L(LA251)  
 Step-L(LA247)  
 Step-S(LA247)  
 Blast-S(LA247)  
 Other: Step-M

**Body**  
 Trident:RB5(UMB01)  
 Sword:RB5SP(UMB02)  
 Other: \_\_\_\_\_

**Battery Placement**  
 Front  Rear

**Weight Placement** \* 1oz=28g

Ride Height  A  B F 24 mm R 23.5 mm

**Truck Condition**

<input type="checkbox"/> Smooth	<input type="checkbox"/> Sandy
<input type="checkbox"/> Bumpy	<input type="checkbox"/> Soft Dirt
<input type="checkbox"/> Low Traction	<input type="checkbox"/> Grass
<input type="checkbox"/> Med. Traction	<input type="checkbox"/> Blue Groove
<input type="checkbox"/> High Traction	<input type="checkbox"/> Clay
<input type="checkbox"/> Wet	<input type="checkbox"/> Dusty
<input type="checkbox"/> Dry	<input type="checkbox"/> Other

**Kind in spring**

#55	Orange
#60	Orange Yellow
#65	Yellow
#68	Blue
#70	Silver
#72	Cobalt blue
#75	Light Green
#80	Green

Tire	Front	Rear
Tire	_____	_____
Inserts	_____	_____
Wheel	_____	_____
Traction Compound	_____	_____

**Others** gear ratio =2.6

Motor ORION 2009 7.5T

Pinion/Spur 22 / 78

Battery PEAK 5400 Lipo

ESC Much More FLETA3.0

Comment :

\_\_\_\_\_

\_\_\_\_\_