

EVOLVA 2007

SETTING DATA SHEET Ver 1.00

NAME	Team KYOSHO	TEMP	°C	ENGINE		MUFFLER	
DATE	2007/04/10	HUMIDITY	%	HEAD CLEARANCE	mm	FUEL TYPE	
TRACK		TRACTION	%	PLUG No.		RADIO	

Diagram of front suspension components including servo saver, scrub set, and various adjustment points labeled H, M, V, and 1.5, 5, 7.

SHOCK OIL	400 450 500 550 600 700 800
DIAPHRAGM	(N) (W6006)
SHOCK PISTON	(N) Φ 1.2-1Hole
SPRING	1.8 (1.9) 2.0 White
SPRING ADJUSTER	mm
SHOCK POS	(H) M V
SCRUB SET (FMW20-1)	0.5 (1.0) 1.0 (FMW20)
CASTER ANGLE / W.B	11° / Normal (Short)
CAMBER ANGLE	L 0 (0.5) 1 1.5 2 2.5 3 R 0 (0.5) 1 1.5 2 2.5 3
TOE ANGLE	-1°
FRONT WIDTH OG (1G)	252 mm
UP STOP	- mm
DOWN STOP	0 mm
ANTIROLL BAR VZ084	(VZ084S)
TIRE HARDNESS	(32) 35 37 40
TIRE TYPE	KYOSHO TYRE
TIRE DIAMETER	ϕ 69 mm
ROAD CLEARANCE	7.5 mm

Diagram of rear suspension components including servo saver, scrub set, and various adjustment points labeled 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100.

SHOCK OIL	400 450 500 550 600 700 800
DIAPHRAGM	(N) (W6006)
SHOCK PISTON	(N) Φ 1.1-2Hole
SPRING	1.8 1.9 (2.0) White
SPRING ADJUSTER	mm
SHOCK POS	0 (1) 2 3
SCRUB SET	0.5 1.0 (1.5) 2.0
UPPER ARM LONG (SHORT)	(IN) OUT 2 mm
CAMBER ANGLE	L 0 (0.5) 1 1.5 2 2.5 3 3.5 R 0 (0.5) 1 1.5 2 2.5 3 3.5
TOE ANGLE	+2.0°
REAR WIDTH OG (1G)	262 mm
UP STOP	- mm
DOWN STOP	9 mm
ANTIROLL BAR / POS	(3) / ϕ 3 mm
TIRE HARDNESS	32 (35) 37 40
TIRE TYPE	KYOSHO TYRE
TIRE DIAMETER	ϕ 76 mm
ROAD CLEARANCE	8 mm
SUS HOLDER	7 / 7-2in / (7-3.5in)

CLUTCH TYPE	2D (3D) 4D	PINION GEAR	15 (16) 17 / 19 (20) 21
CLUTCH SHOE	BLACK RED (GREY)	SPUR GEAR	48 (49) / 44 (45)
CENTRIFUGAL SHOE	(N)	DRIVE RATIO	(mm Difference) 26/18 (420 BELT)
CLUTCH SPRING	4D	CENTER POST POSITION	0 / 1 / 2 / (3)
CLEARANCE	0.5 mm	BODY MOUNT ANGLE	0 / 1 / (2)
ADJ. NUT	1 mm	BODY MOUNT HEIGHT	L / (H) (0) / 3
MEMO			