

NAME			TEMP	°C	ENGINE			MUFFLER		
DATE			HUMIDITY	%	HEAD CLEARANCE	mm		FUEL TYPE		
TRACK			TRACTION	%	PLUG No.			RADIO		

SHOCK OIL	400 450 500 550 600 700 800
DIAPHRAGM	N
SHOCK PISTON	N
SPRING	1.8 1.9 2.0
SPRING ADJUSTER	mm
SHOCK POS	H M V
SCRUB SET (FMW20-1)	0.5 1.0 1.0 (FMW20)
CASTER ANGLE / W.B	° / Normal Short
CAMBER ANGLE	L 0 0.5 1 1.5 2 2.5 3 R 0 0.5 1 1.5 2 2.5 3
TOE ANGLE	°
FRONT WIDTH OG/1G	mm
UP STOP	mm
DOWN STOP	mm
ANTIROLL BAR	VZ084 VZ084S
TIRE HARDNESS	32 35 37 40
TIRE TYPE	
TIRE DIAMETER	φ mm
ROAD CLEARANCE	mm

SHOCK OIL	400 450 500 550 600 700 800
DIAPHRAGM	N
SHOCK PISTON	N
SPRING	1.8 1.9 2.0
SPRING ADJUSTER	mm
SHOCK POS	0 1 2 3
SCRUB SET	0.5 1.0 1.5 2.0
UPPER ARM	LONG/SHORT IN/OUT mm
CAMBER ANGLE	L 0.5 1 1.5 2 2.5 3 3.5 R 0.5 1 1.5 2 2.5 3 3.5
TOE ANGLE	°
REAR WIDTH OG/1G	mm
UP STOP	mm
DOWN STOP	mm
ANTIROLL BAR /POS	φ 3 / ○ mm
TIRE HARDNESS	32 35 37 40
TIRE TYPE	
TIRE DIAMETER	φ mm
ROAD CLEARANCE	mm

GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL
15/48	7.68	15/49	7.84	19/44	5.56	19/45	5.68
16/48	7.20	16/49	7.35	20/44	5.28	20/45	5.40
17/48	6.78	17/49	6.92	21/44	5.03	21/45	5.14

CLUTCH TYPE	2D 3D 4D	PINION GEAR	15 16 17 / 19 20 21
CLUTCH SHOE	BLACK RED GREY	SPUR GEAR	48 49 / 44 45
CENTRIFUGAL SHOE	N	DRIVE RATIO	7mm Difference 26/18(420 BELT)
CLUTCH SPRING		CENTER POST POSITION	0 / 1 / 2 / 3
CLEARANCE	mm	BODY MOUNT ANGLE	0 / 1 / 2
ADJ. NUT	mm	BODY MOUNT HEIGHT	L / H 0 / 3

MEMO